



Enterprise class A4 mono printers for improved business efficiency

The ES7131 A4 mono printer brings fast, reliable printing to the busy workgroup by combining advanced security, management and performance with robust and durable LED technology.

It offers print speeds of up to 52ppm for enhanced office efficiency and improves workgroup productivity by deploying a fast processor with ample memory to tackle complex and high volume print jobs.

First page out times are as little as 5 seconds and the ES7131 offers a flexible paper source with multiple input trays and a maximum input capacity of 3,160 sheets. The versatile engine has a monthly duty cycle of 200K prints and can confidently handle a variety of applications in any working environment.

The ES7131 has a high yield toner cartridge for reduced user intervention rates and its wireless connection adds versatility by allowing the unit to be placed wherever is most convenient.

Improving business productivity

- Up to 52ppm print speed and time to first print, less than 5 seconds
- Duplex as standard, for in-house professional printing
- Paper capacity of up to 3,160 sheets
- High yield toner cartridges

Fast Processing

- 800MHz processor and 256MB RAM memory
- Optional 160GB Hard Disk Drive
- Wireless connectivity as standard
- 10/100/1000 baseT Ethernet

Excellent print quality

- 1200 x 1200dpi print resolution ensures pinsharp output every time
- Flexible media handling - up to 253gsm and 1.3m banners

Highest level document and data security

Including security and encryption to the highest industry standards, the ES7131dnw provides sophisticated user authentication that prevents unauthorised access and protects your corporate data.

- Secure Print job encryption
- SNMPv3 and IPSec secure networking
- 802.1X network protocol and IP/MAC filtering access control
- Secure Print with numeric keypad for easy PIN code entry

Reducing your impact on the environment

OKI technology and in-built eco features ensure that the ES7131dnw is both efficient and environmentally friendly.

- Double sided printing for reduced paper usage
- High capacity toner cartridges
- Toner save function
- 3.9W or less in Deep Sleep mode
- Energy Star certified

Mobile printing

Print effortlessly from your smartphone or tablet. This printer is compatible with AirPrint by Apple Inc, Cortado Workplace and ePrint by Microtech Corp, enabling you to print where ever you are, without having to connect directly to a printing device.



ES7131dnw - Mono Printer

PRINT	
A4 Print speed	52ppm
Time to first print	Less than 5 seconds
Warm up time	60 seconds from power on, 19 seconds or less from power save
Processor speed	800MHz

PRINT QUALITY	
Resolution	1200 x 1200dpi, 600 x 600dpi

TYPEFACES	
Printer fonts	Scalable: 87 PCL fonts & 136 PostScript fonts, Line Printer, OCR-A/B, USPS ZIP Barcode
Dot matrix fonts	Epson FX, IBM-PPR
Barcode	10 types of one dimension with 26 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET, 2 types of two dimensions: PDF417, QRcode

INTERFACE AND SOFTWARE	
Connectivity	10/100/1000 baseT, Wireless LAN 802.11b/g/n, High Speed USB x 2 (1x type A & 1x type B)
Printer languages	PCL5e, PCLX, Postscript 3 Emulation, XPS, Epson FX, IBM PPR
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP v4 & v6, Net Bios over TCP, SMTP, HTTP, HT-TPS, SNMP v1 & v3, DHCP, DNS, IPP, IPPS, BOOTP, DDNS, WINS, UPnP, SNMP, IGMP, IGMP v2, ICMP, IMCP v6, LPR, Port9100, FTP, Telnet, Bonjour, LLTD, Web Service on Devices, AirPrint, Wireless LAN Protocol (IEEE802.11b, IEEE802.11g, IEEE802.11n, Infrastructure Mode, WEP, WPA(TKIP), WPA2(AES), WPS-PBC, WPS-PIN, Open system authentication, Shared key authentication, IEEE802.1x authentication)
OS Compatibility ¹	Windows 8 (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit) / Vista SP1 & SP2 (32-bit & 64-bit) / XP SP2 or later / Server 2008 SP1 or later (32-bit & 64-bit) / Server 2003 SP2 (32-bit & 64-bit) / Server 2008 R2 (64-bit); Mac OS X 10.4/10.5/10.6/10.7/10.8; PPDs for Linux/Unix
Utility suite ¹	Print Job Accounting ² , Print Job Accounting Client ² , PrintSuperVision.NET ² , Template Manager ² , Universal PCL Print Driver ² , Configuration Tool ² , OKI LPR Utility ² , PDF Direct Print ²

SECURITY	
Device Security	IP Filtering, MAC Filtering, IPSec, Secure Print, Secure Print job encryption, SMTP server authentication, SNMPv3, SSL/TLS Encryption, Port Change, Storage Device Encryption, Secure Erase, Disable Host USB feature, Protocol ON/OFF
Certification	CE Mark, Energy Star, GS Mark

PAPER HANDLING	
Standard Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm
Optional Paper capacity	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; Tray 4: 530 sheets of 80gsm; Large Capacity Feeder: 2,000 sheets of 80gsm
Paper Input capacity	Standard: Up to 630 sheets of 80gsm; Maximum: Up to 3,160 sheets of 80gsm
Paper sizes	Tray 1: A4, A5, B5; Tray 2/3/4: A4, A5, B5; Large Capacity Feeder: A4; Multi-purpose tray: A4, B5, A5, A6. Envelopes (Com-9, Com10, DL, C5), Supports custom size: Width 76-216mm Length 127-1321mm; Duplex: A4, B5. Supports custom size: Width 148-216mm Length: 210-356mm
Paper weight	Tray 1: 64 to 220gsm; Tray 2/3/4: 64 to 220gsm; Large Capacity Feeder: 64 to 220gsm; Multi-purpose tray: 64 to 253gsm; Duplex: 64 to 220gsm
Duplex	Standard
Paper output	Face up: 100 sheets of 80gsm, Face down: 500 sheets of 80gsm

GENERAL FEATURES	
Memory	Standard RAM: 256MB; Maximum RAM: 768MB Optional HDD: 160GB
Environment	Operating temperature/ humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended) Storage temperature/ humidity: -10°C to 43°C / 10% to 90% RH
Power supply	Single phase 220-240VAC, frequency 50/60Hz +/- 2%
Power consumption	Typical: 850W; Max: 1400W; Idle: 95W; Power Save: 22W; Deep Sleep: 3.9W or less
Noise level	Operating: 57dB(A) or less; Quiet Mode: 53dB(A); Standby: 30dB(A); Power save: Background level
Dimensions (HxWxD)	410 x 435 x 498mm
Weight ³	27kg approx
Product order number	ES7131dnw: 01334201

ACCESSORIES (ORDER NUMBERS)	
Paper Feeders	2nd/3rd/4th paper tray: 45478902; Large Capacity Feeder: 45530102
Castor base	45478702
Hard Disk Drive	160GB: 44622305
Memory	512MB: 01182908

CONSUMABLES (ORDER NUMBERS)	
Toner cartridge* (36,000 pages)	45460502
Image drum* (72,000 pages)	45456302
Maintenance Kit (200,000 pages)	45435104

*Toner: Number of A4 pages @ ISO/IEC 19752 coverage.
Printer shipped with toner for 36,000 pages @ ISO/IEC 19752.

¹Check local OKI Executive Series website for latest driver releases and OS compatibility; ²Windows only; ³Including all consumables

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.



CORTADO
Business Class of Cloud Desktop Services

OKI SYSTEMS (UK) LTD
Blays House, Wick Road
Egham, TW20 0HJ
United Kingdom
T +44(0) 1784 274300
F +44(0) 1784 274301

WWW.OKIEXECUTIVESERIES.CO.UK

OKI

Open up your dreams